



designed for scientists



RCT basic PT Wireless Solution

/// Data Sheet

More features, more flexibility – wireless and secure

The RCT basic PT Wireless Solution expands the trusted RCT basic with additional features for wireless temperature and pH measurement. The system combines precise measurement technology with enhanced security and maximum flexibility in everyday laboratory work.

Wireless data transmission

The USB WD wireless dongle included in the scope of delivery enables the wireless transmission of measurement data. The central system component is the PT Wireless Sensor, also included, which transmits temperature data wirelessly to



designed for scientists

the RCT basic.

A pH electrode can optionally be connected to the PT Wireless via a BNC connector. In this configuration, the RCT basic becomes a pH meter:

The pH value can be displayed directly on the screen – without the need for an additional external measuring device.

Another advantage of the wireless sensor technology:

No cables are required on the temperature sensor – damaged or burnt sensor cables are a thing of the past.

Alternatively, the Wireless Dongle USB WD also allows connection to the IKA 'Lab Assistant' app for visualising measurement data.

Increased safety through dual temperature measurement

In combination with the wired temperature sensor PT 1000.60, which is also included in the scope of delivery, two temperatures can be measured simultaneously:

- PT 1000.60 (wired): Monitoring and limiting the temperature of a heat transfer medium, e.g. synthesis block, oil, water or sand bath
- PT Wireless: Temperature control directly within the reaction medium

This configuration enhances the safety of the experiment, particularly in the event of glass breakage.

The RCT basic automatically displays both temperatures side by side on the screen.

Complete solution including mounting hardware

All the necessary mounting hardware is included in the scope of delivery to ensure secure and flexible positioning of the wireless sensor (stand, support rod and boss head clamp).

Scope of delivery

- RCT basic
- IKAFLON® 30 Magnetic stirring bar
- IKAFLON® 40 Magnetic stirring bar
- PT wireless Wireless Sensor
- USB WD USB Dongle RCT
- H 16 V Support rod
- PT 1000.60 Temperature sensor, stainless steel
- H 38 Holding rod
- H 44 Boss head clamp
- H 80 Temperature sensor holder
- Screwdriver



designed for scientists

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	20
Maximum load [kg]	25
Motor rating output [W]	9
Motor principle	Brushless DC
Direction of rotation	right
Speed display set-value	LED
Speed display actual-value	LED
Speed adjustment	Control knob (Rotating / Pressing)
Speed range [rpm]	50 - 1500
Setting accuracy speed [rpm]	10
Stirring bar length [mm]	20 - 80
Self-heating of the set-up plate by max. stirring (RT:22°C/duration:1h) [K]	+12
Heat output [W]	800
Temperature display set-value	LED
Temperature display actual-value	LED
Temperature unit	°C
Heating temperature range [°C]	Room temp. + device self heating - 310
Heat control	Control knob (Rotating / Pressing)
Display resolution [K]	0.1
Temperature setting range [°C]	0 - 310
Temperature setting resolution of heating plate [K]	1
Connection for ext. temperature sensor	PT1000, ETS-D5, ETS-D7, PT wireless
Temperature setting resolution of medium [K]	1
Operating temperature min. (with external cooling) [°C]	-20
Adjustable safety circuit [°C]	50 - 360
Set-up plate material	Aluminium alloy
Set-up plate dimensions [mm]	Ø 135
Timer	yes
Timer display	LED
Time setting min. [s]	1
Time setting max. [min]	5999
pH measurement	optional (with ETS-D7, PT wireless)
Sensor in medium detection	yes
Temperature measure range PT1000 [°C]	-20 - 310
PT 1000 deviation;DIN EN 60751 Kl. A [K]	≤ ± (0.15 +0.002x T)
Speed deviation (no load,nominal voltage, at 1500rpm + 25 °C) [%]	±2
Heating rate (1l H ₂ O in H1500) [K/min]	9
Heat control accuracy of heating plate centre without vessel (at 100°C) [K]	±5
Heat control accuracy with ext. PT1000 (500ml H ₂ O in 600ml beaker,40mm stirring bar,600rpm,50°C) [K]	±0.5
Heat control accuracy with ETS-D5 (500ml H ₂ O in 600ml beaker,40mm stirring bar,600rpm,50°C) [K]	±0.5
Heat control accuracy with ETS-D7 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [K]	±0.2
Heat control accuracy with PT wireless (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [K]	±0.2
Dimensions (W x H x D) [mm]	160 x 100 x 200
Weight [kg]	2.3
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 54



designed for scientists

RS 232 interface	yes
USB interface	USB-C
WPAN interface	optional (USB WD)
Voltage [V]	220 - 230
Frequency [Hz]	50/60
Power input [W]	820
Power input standby [W]	0.45