



## **CRUSH TESTER**

model CT-2000



The CT-2000 determines the compression strength of corrugated fibreboard and its components for Q.C. (quality control) and R&D (research and development).

This equipment is absolutely user friendly and its operation can easily be done through its built-in testing software, alphanumeric backlighted display and membrane keyboard.

It offers complete statistics, a parallel port for the connection of a local printer and a RS-232 serial port for the connection to a computer.

Major Technical Characteristics		
Capacity	4000 N	
Resolution	0,1 N	
Selectable testing units	N, kgf or lbf	
Testing speed (programmable)	10 - 40 mm/min	
Return speed of plates	250 mm/min	
Stroke length (programmable)	5 - 80 mm	
Rupture level (programmable)	40 - 100%	
Stroke length (programmable)	5 - 80 mm	

The CT-2000 also features lightweight cast-aluminium body, HBM high precision load cell, sturdy steel niquel-platted testing plates, heavy duty step motor, STAR accurate ball screw, built-in electronics and exclusive testing software for each test.

Test	ACESSORY REQUIRED	TECHNICAL STANDARD
Flat Crush Test (FCT)	Circular Cutter - CT-CA	ISO 3035/TAPPI T-825
Ring Crush Test (RCT)	Ring Crush Holder - CT-RA	ISO 12192/TAPPI T-822
Corrugated Crush Test (CCT)	Corrugated Crush Test Device - CT-CO	TAPPI T-843
Concora Medium Test (CMT)	Laboratory Fluter - LF-21	ISO 7263/TAPPI T-809
Pin Adhesion Test (PAT)	Pin Adhesion Test Device - CT-AC	TAPPI T-821
Edge Crush Test ISO (ECT)	Edgewise Blocks ISO - ECT	ISO 3037
Short Column Test TAPPI (SCT)	Edgewise Blocks TAPPI - SCT	ISO 13821/TAPPI T-811
Short Column Test TAPPI (SCT 839)	Clamp Fixture TAPPI - SCT T-839	TAPPI T-839

Some tests require also the use of specific sample preparation equipment, like 2G-15 used to prepare stripe test pieces for RCT, CCT and CMT tests, and like the CAP-21 used to prepare test pieces for ECT, SCT and PAT tests.

Applicable Standards: ISO 13820

Power Supply	220 VCA, 50/60 Hz, single phase, 200 W
Dimensions	(320 x 320 x 560) mm (W x L x H)
Weight	50 kg

Note: due to constant development our equipment design and specifications are subject to change without notice.

Address: Av. Dr. Alberto Jackson Byington, 1595 · CEP: 06276-000 - Osasco - SP - Brazil Phone: +55 11 3601 5700 · Fax: +55 11 3601 5973 · e-mail: regmed@regmed.com.br www.regmed.com.br